



Engine Info:

Stroke	3.622 in
Rod Length	6.098 in
H Gasket Thick	0.051 in
Out of hole	0.005 in
Rocker R	1.7 :1
Valve Angle	15 d
Lobe Seperation	112 d
Advance	d
Bore Size	3.78 in
Ideal Compression R	9.5 :1
Head Chamber Volume	61.2 ~cc

Piston to Valve Clearance Information

Required Valve drop for	0.050 P2V
Min Valve drop I	0.086 in
Min Valve drop E	0.111 in
IValve To Zero Deck	0.036 in
EValve To Zero Deck	0.061 in

Want more or less P2V clearance? Simply add the amount of Piston to Valve Clearance you would like to "Ivalve to Zero Deck"/"Evalve to Zero Deck" ALWAYS CHECK P2V

Cam Info

Specs	218 / 228 112 + 0
Lift	0.527 0.5389

Valve Events

	.@ 0.05	.@ 0.006
EVO	46	73
EVC	-2	-29
IVO	3	-24
IVC	41	68
Overlap	-1	53
ICL	112	
ECL	112	

Lobe Data

Basecircle

Duration

Tappet Lift @ TDC

Valve lift @ '0' lash,
rocker arm ratio

Lobe Key	C2722180.31	CC2822280.317
Manufacturer	Comp Cams	Comp Cams
Key	CC	CC
Type	RPM Low Lift	Xtreme RPM Low Lift
Lobe#	3752	3755
Dia		
0.004		
0.006	272	282
0.015		
0.020		
0.050	218	228
0.200	132	141
Lobe Lift	0.310	0.317
102		
104		
106	0.059	0.075
110	0.048	0.062
114		
1.7	0.527	0.539
1.72	0.533	0.545
1.75	0.543	0.555
1.8	0.558	0.571
1.82	0.564	0.577
1.85	0.574	0.586

