



Engine Info:

Stroke	3.622 in
Rod Length	6.098 in
H Gasket Thick	0.051 in
Out of hole	0.005 in
Rocker R	1.7 :1
Valve Angle	15 d
Lobe Seperation	112 d
Advance	d
Bore Size	3.78 in
Ideal Compression R	9.5 :1
Head Chamber Volume	61.2 ~cc

Piston to Valve Clearance Information

Required Valve drop for	0.050 P2V
Min Valve drop I	0.101 in
Min Valve drop E	0.131 in
IValve To Zero Deck	0.051 in
EValve To Zero Deck	0.081 in

Want more or less P2V clearance? Simply add the amount of Piston to Valve Clearance you would like to "Ivalve to Zero Deck"/"Evalve to Zero Deck" ALWAYS CHECK P2V

Cam Info

Specs	224 / 236 112 + 0
Lift	0.5338 0.544

Valve Events

	.@ 0.05	.@ 0.006
EVO	50	77
EVC	-6	-33
IVO		-27
IVC	44	71
Overlap	6	60
ICL	112	
ECL	112	

Lobe Data

Basecircle

Duration

Tappet Lift @ TDC

Valve lift @ '0' lash,
rocker arm ratio

Lobe Key	2782240.314	CC2902360.32
Manufacturer	Comp Cams	Comp Cams
Key	CC	CC
Type	RPM Low Lift	Xtreme RPM Low Lift
Lobe#	3753	3757
Dia		
0.004		
0.006	278	290
0.015		
0.020		
0.050	224	236
0.200	137	147
Lobe Lift	0.314	0.320
102		
104		
106	0.069	0.088
110	0.056	0.075
114		
1.7	0.534	0.544
1.72	0.540	0.550
1.75	0.550	0.560
1.8	0.565	0.576
1.82	0.571	0.582
1.85	0.581	0.592

Fitted Lobe vs Closest P2V

