



Engine Info:

Stroke	3.622 in
Rod Length	6.098 in
H Gasket Thick	0.051 in
Out of hole	0.005 in
Rocker R	1.7 :1
Valve Angle	15 d
Lobe Seperation	113 d
Advance	d
Bore Size	4 in
Ideal Compression R	10.1 :1
Head Chamber Volume	72.4 ~cc

Cam Info

Specs	226 / 236 113 + 0
Lift	0.5355 0.544

Piston to Valve Clearance Information

Required Valve drop for	0.050 P2V
Min Valve drop I	0.101 in
Min Valve drop E	0.126 in
IValve To Zero Deck	0.051 in
EValve To Zero Deck	0.076 in

Want more or less P2V clearance? Simply add the amount of Piston to Valve Clearance you would like to "Ivalve to Zero Deck"/"Evalve to Zero Deck" ALWAYS CHECK P2V

Valve Events

	.@ 0.05	.@ 0.006
EVO	51	78
EVC	-5	-32
IVO		-27
IVC	46	73
Overlap	5	59
ICL	113	
ECL	113	

Lobe Data

Basecircle

Duration

Tappet Lift @ TDC

Valve lift @ '0' lash,
rocker arm ratio

Lobe Key	2802260.315	CC2902360.32
Manufacturer	Comp Cams	Comp Cams
Key	CC	CC
Type	RPM Low Lift	Xtreme RPM Low Lift
Lobe#	3754	3757
Dia		
0.004		
0.006	280	290
0.015		
0.020		
0.050	226	236
0.200	139	147
Lobe Lift	0.315	0.320
102		
104		
106	0.072	0.088
110	0.059	0.075
114		
1.7	0.536	0.544
1.72	0.542	0.550
1.75	0.551	0.560
1.8	0.567	0.576
1.82	0.573	0.582
1.85	0.583	0.592

Fitted Lobe vs Closest P2V

