



Engine Info:

Stroke	3.622 in
Rod Length	6.098 in
H Gasket Thick	0.051 in
Out of hole	0.005 in
Rocker R	1.7 :1
Valve Angle	15 d
Lobe Seperation	118 d
Advance	d
Bore Size	4.065 in
Ideal Compression R	10.5 :1
Head Chamber Volume	70.2 ~cc

Piston to Valve Clearance Information

Required Valve drop for	0.050 P2V
Min Valve drop I	0.052 in
Min Valve drop E	0.076 in
IValve To Zero Deck	0.002 in
EValve To Zero Deck	0.026 in

Want more or less P2V clearance? Simply add the amount of Piston to Valve Clearance you would like to "Ivalve to Zero Deck"/"Evalve to Zero Deck" ALWAYS CHECK P2V

Cam Info

Specs	212 / 224 118 + 0
Lift	0.5202 0.5338

Valve Events

	.@ 0.05	.@ 0.006
EVO	50	77
EVC	6	-21
IVO	12	-15
IVC	44	71
Overlap	-18	36
ICL	118	
ECL	118	

Lobe Data

Basecircle

Duration

Tappet Lift @ TDC

Valve lift @ '0' lash,
rocker arm ratio

Lobe Key	2662120.306	CC2782240.314
Manufacturer	Comp Cams	Comp Cams
Key	CC	CC
Type	RPM Low Lift	Xtreme RPM Low Lift
Lobe#	3751	3753
Dia		
0.004		
0.006	266	278
0.015		
0.020		
0.050	212	224
0.200	126	137
Lobe Lift	0.306	0.314
102		
104		
106	0.051	0.069
110	0.040	0.056
114		
1.7	0.520	0.534
1.72	0.526	0.540
1.75	0.536	0.550
1.8	0.551	0.565
1.82	0.557	0.571
1.85	0.566	0.581

Fitted Lobe vs Closest P2V

