



Engine Info:

Stroke	3.622 in
Rod Length	6.098 in
H Gasket Thick	0.051 in
Out of hole	0.005 in
Rocker R	1.7 :1
Valve Angle	15 d
Lobe Seperation	114 d
Advance	d
Bore Size	4.065 in
Ideal Compression R	10.5 :1
Head Chamber Volume	70.2 ~cc

Cam Info

Specs	220 / 236 114 + 0
Lift	0.5304 0.544

Piston to Valve Clearance Information

Required Valve drop for	0.050 P2V
Min Valve drop I	0.083 in
Min Valve drop E	0.122 in
IValve To Zero Deck	0.033 in
EValve To Zero Deck	0.072 in

Want more or less P2V clearance? Simply add the amount of Piston to Valve Clearance you would like to "Ivalve to Zero Deck"/"Evalve to Zero Deck" ALWAYS CHECK P2V

Valve Events

	.@ 0.05	.@ 0.006
EVO	52	79
EVC	-4	-31
IVO	4	-23
IVC	44	71
Overlap		54
ICL	114	
ECL	114	

Lobe Data

Basecircle

Duration

Tappet Lift @ TDC

Valve lift @ '0' lash,
rocker arm ratio

Lobe Key	2742200.312	CC2902360.32
Manufacturer	Comp Cams	Comp Cams
Key	CC	CC
Type	RPM Low Lift	Xtreme RPM Low Lift
Lobe#	3767	3757
Dia		
0.004		
0.006	274	290
0.015		
0.020		
0.050	220	236
0.200	134	147
Lobe Lift	0.312	0.320
102		
104		
106	0.062	0.088
110	0.051	0.075
114		
1.7	0.530	0.544
1.72	0.537	0.550
1.75	0.546	0.560
1.8	0.562	0.576
1.82	0.568	0.582
1.85	0.577	0.592

Fitted Lobe vs Closest P2V

