



Engine Info:

Stroke	3.622 in
Rod Length	6.098 in
H Gasket Thick	0.051 in
Out of hole	0.005 in
Rocker R	1.7 :1
Valve Angle	15 d
Lobe Seperation	113 d
Advance	d
Bore Size	4.065 in
Ideal Compression R	10.5 :1
Head Chamber Volume	70.2 ~cc

Piston to Valve Clearance Information

Required Valve drop for	0.050 P2V
Min Valve drop I	0.111 in
Min Valve drop E	0.133 in
IValve To Zero Deck	0.061 in
EValve To Zero Deck	0.083 in

Want more or less P2V clearance? Simply add the amount of Piston to Valve Clearance you would like to "Ivalve to Zero Deck"/"Evalue to Zero Deck" ALWAYS CHECK P2V

Cam Info

Specs	230 / 240 113 + 0
Lift	0.5389 0.5304

Valve Events

	.@ 0.05	.@ 0.006
EVO	53	79.5
EVC	-7	-33.5
IVO	-2	-29
IVC	48	75
Overlap	9	62.5
ICL	113	
ECL	113	

Lobe Data

Basecircle

Duration

Tappet Lift @ TDC

Valve lift @ '0' lash,
rocker arm ratio

Lobe Key	2842300.317	CC2932400.312
Manufacturer	Comp Cams	Comp Cams
Key	CC	CC
Type	RPM Low Lift	Cheater HR
Lobe#	3735	3392
Dia		
0.004		
0.006	284	293
0.015		
0.020		
0.050	230	240
0.200	142	152
Lobe Lift	0.317	0.312
102		
104		
106	0.078	0.091
110	0.065	0.078
114		
1.7	0.539	0.530
1.72	0.545	0.537
1.75	0.555	0.546
1.8	0.571	0.562
1.82	0.577	0.568
1.85	0.586	0.577

